# Product information
Rapid Cleaner

PI 22/08/18/2026

## Description
A combination of selected acetone-free solvents for the rapid, efficient cleaning and degreasing of components in motor vehicles and industrial applications. The low surface tension of this product gives it excellent penetration properties, enabling it to dissolve oil, grease, resin and tar residues and contaminants easily, even in hidden areas. After the solvent has evaporated, the surface is left free of grease and residues.




## Properties
- universal application
- optimizes economical use
- high proportion of active components
- absolutely free of chlorine
- low surface tension
- controlled evaporation free of residues
- optimum penetration capacity
- removes oil and grease-based contaminants
- dissolves resin and tar-type residues
- leaves no residues
- contains no acetone

## Technical data

| | |
|---|---|
| Color / appearance | colourless |
| Flash point | -17 °C |
| Density | 0,72 g/cm³ |
| Base | solvent mixture, acetone-free |
| Form | liquid |

## Areas of application
**Automotive area:**
**Brakes:** Drum and disk brakes, linings, shoes, cylinders, springs and pads.
**Clutch:** Clutch linings, pressure plate and clutch components in general.
**Transmission:** Automatic gear change, planet carriers, oil pump, brake bands, clutches and gearwheels.
**Assembly and repair:** Carburetor, gasoline pump, engine components, electrical systems such as controllers, alternator and starter. Removes oil and grease spots from floor coverings, materials and linings.

## Comment
As this is an industrial product, it may contain traces of denatured alcohol such as isopropanol/ethanol.

## Application
Spray contaminated components and allow to drain. After the solvent has evaporated, the components will be clean and free of grease.

**Note:** Product may attack paints and plastic components. Check for material compatibility before using!

## Available pack sizes

| | |
|---|---|
| 5 l Canister plastic | 1840<br>AR-DE-EL-FR-NL |
| 5 l Canister plastic | 2824<br>DA-EN-FI-NO-SV |
| 5 l Canister plastic | 3319<br>DE-EN-IT |
| 20 l Canister plastic | 21285<br>AUEN-EN |
| 60 l Black plate barrel | 3333<br>DE-EN |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com