

Brake & Parts Cleaner

Description

The combination of select acetone free solvents provides quick and efficient removal of grease and dirt from contaminated surfaces and can be used in automotive and industrial applications as well as in other industries. Thanks to its low surface tension it will easily penetrate into and behind deposits like oil, grease and sticky substances to completely dissolve these, even in hidden areas. Once evaporated it will leave behind a dry, grease and oil free surface.

Properties

- optimizes economical use
- high proportion of active components
- leaves no residues
- low surface tension
- dissolves resin and tar-type residues
- controlled evaporation free of residues
- optimum penetration capacity
- contains no acetone
- universal application
- removes oil and grease-based contaminants
- absolutely free of chlorine

Technical data

Color / appearance	colourless
Flash point	1 °F
Density	0,72 g/cm ³
Base	solvent mixture, acetone-free
Form	liquid

Areas of application

Automotive area:

Brakes: Drum and disc brakes, linings, shoes, cylinders, springs and pads.

Clutch: Clutch components, pressure plates, discs etc.

Transmission: Valve body, gears, clutch packs, oil pumps, brake bands, solenoids, shafts etc.

Assembly and repair: Carburetor, fuel pump, components, electrical controls, alternator, starter etc. Also clean floors, tools, equipment etc.

Industrial areas: Removes stubborn deposits such as oil, grease, silicone, permanent marker ink, chafed rubber and wax. Use on sensitive materials such as stainless, copper and aluminum alloys.

Comment

As this is an industrial product, it may contain traces of denatured alcohol such as isopropanol/ethanol.



Not for sale in the following states: CA, CO, CT, DE, IL, IN, MD, MA, ME, MI, NJ, NH, NY, OH, PA, RI, UT, VA, WA. May not be legal for use or sale in other areas. Check local regulations.

Application

Treat contaminated components and allow to drain. After the solvent has evaporated, the components will be clean and free from grease.

May affect paints and plastic. Test on inconspicuous surface before use.

Available pack sizes

196 l Black plate barrel 22236
USA-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.