Product information

PI 52/11/13/2026

Top Tec ATF 1200



Description

Fully synthetic automatic transmission fluid with modern additive technology provides high thermal stability, excellent wear protection and correct friction behavior. Excellent low temperature behavior. Compatible with most common seal materials.

Properties

- excellent wear protection
- optimum stability to aging
- excellent corrosion protection
- excellent viscosity/temperature properties
- outstanding friction characteristics
- very good low-temperature properties
- highest thermal stability
- high chemical resistance
- enables a multifaceted range of applications

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Allison C4 • Allison TES 295 • BMW 7045 E • BMW 8072 B • BMW LA 2634 • BMW LT 71141 • Caterpillar TO-2 • Chrysler ATF +3 • Chrysler ATF +4 • Daimler NAG-1 • Dexron III H • Ford Mercon V • Honda ATF Z1 (except CVT) • Hyundai SP-II • Hyundai SP-III • JASO 1-A • JWS 3309 (Aisin Warner) • Kia SP-II • Kia SP-III • MAN 339 Typ V1 • MAN 339 Typ Z1 • MAN 339 Typ Z2 • Mazda ATF M-III • Mazda ATF M-V • MB 236.2 • MB 236.5 • MB 236.6 • MB 236.7 • MB 236.9 • MB 236.10 • MB 236.11 • MB 236.91 • Mitsubishi SP-II • Mitsubishi SP-III • Nissan AT-Matic D Fluid • Nissan AT-Matic J Fluid • Nissan AT-Matic K Fluid • Subaru ATF • Toyota Type T-II • Toyota Type T-IV • Voith H55.6335.XX (G 607) • Volvo 97340 • Volvo 97341 • VW G 052 162 • VW G 052 990 • VW G 055 025 • ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 05L • ZF TE-ML 09 • ZF TE-ML 11A • ZF TE-ML 11B • ZF TE-ML 14A • ZF TE-ML 14B • ZF TE-ML 17C

Technical data

Density at 59 °F	0,850 g/cm³ DIN 51757
Viscosity at 104 °F	33,0 mm²/s ASTM D 7042
Viscosity at 212°F	6,5 mm²/s ASTM D 7042
Viscosity at -40 °F (Brookfield)	<= 20000 ASTM D 2983
Viscosity index	155 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016

Technical data

Flash point	392 °F DIN ISO 2592
Color / appearance	red

Areas of application

For automatic transmissions, manual transmissions, power steering systems and hydraulics in automotive and commercial vehicles where a ATF fluid meeting current specifications is required or recommended.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!Optimum efficiency and product performance are only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	20018 CAEN-CAFR-USEN
5 l Canister plastic	20020 CAEN-CAFR-USEN
20 l Canister plastic	20022 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com