Product information
Valve Clean

PI 61/10/29/2026



Description
A combination of active agents, specifically developed to clean and maintain intake valves and the combustion chamber of port- and multi-port fuel injected engines. Restores engine efficiency and protects against corrosion in the fuel system.

Properties
- good corrosion protection
- ideal with turbochargers and catalytic converters
- reduces deposits

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 68 °F	0,816 g/ml
Flash point	>61 °F
Shelf life in original sealed container	60 months

Areas of application
Suitable for use in all 4-stroke gasoline engines with port- and multi-port fuel injection, with or w/o turbochargers. Safe for use with catalytic converters and particulate filters (GPF).

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application
For best results, use Valve Clean regularly. One full can (150 ml) used with 25–75 Liters (7 gal. to 20 gal.) of fuel.

Available pack sizes

150 ml Can sheet metal	2001 USEN
150 ml Can sheet metal	7701 CAEN-CAFR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com