Product information
Top Tec ATF 1900

PI 52/11/13/2026



Description
Fully synthetic, low viscosity automatic transmission fluid, developed to meet the strict requirements of 2nd generation Mercedes-Benz 7-speed automatic transmissions (type 722.9 and 724.2 hybrid). Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a blue color.

Properties
- excellent viscosity/temperature properties
- outstanding friction characteristics
- very good low-temperature properties
- high efficiency

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:
MB 236.15

Technical data

Density at 59 °F	0,845 g/cm³ DIN 51757
Viscosity at 104 °F	20,0 mm²/s ASTM D 7042
Viscosity at 212°F	4,5 mm²/s ASTM D 7042
Viscosity at -40 °F (Brookfield)	⩽ 10000 mPas ASTM D 2983
Viscosity index	145 DIN ISO 2909
Pour point	-59 °F DIN ISO 3016
Flash point	374 °F DIN ISO 2592
Color / appearance	blue to green

Areas of application
For Mercedes-Benz 7-speed automatic transmissions of type 722.9 and 724.2 (hybrid) where an ATF fluid meeting current product specification is required or recommended.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application
Shake well before use. Optimum efficiency and product performance is only possible when the product is used undiluted.Observe the manufacturers instructions!

Available pack sizes

1 l Can plastic	20028 USEN
1 l Can plastic	20360 CAEN-CAFR
20 l Canister plastic	20030 CAEN-CAFR-USEN
1.000 l Container	22220 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com