Product information
Motorbike 4T Bike-Additive

PI 50/10/09/2026



Description

Removes deposits from the fuel system, valves, spark plugs and the combustion chamber while preventing new deposit formation. Improves engine performance and lowers emissions. Provides corrosion protection throughout and prevents carburetor icing.

Properties

- increases operational reliability
- ideal with catalytic converters
- reduces the risk of knocking combustion
- for carburetor and fuel-injection engines
- reduces residue
- prevents corrosion in the fuel system

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 68 °F	0,806 g/ml
Flash point	>61 °F
Shelf life in original sealed container	60 months

Areas of application

Suitable for all 4-stroke gasoline engines. Safe with catalytic converters.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Contents (125 mL) is sufficient for 15–20 Liters (4 gal. to 5.3 gal.) gasoline. Add at every fill-up.

Available pack sizes

125 ml Can sheet metal	20048 USEN
125 ml Can sheet metal	22096 CAEN-CAFR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com