Product information

PI 48/08/18/2026

Motorbike Gear Oil SAE 75W-90



Description

Fully Synthetic, GL5 high-performance extreme-pressure gear oil. Facilitates smooth and precise shifting even in extreme conditions, provides excellent wear protection properties and ideal viscosity-temperature behavior.

Properties

- excellent wear protection
- guarantees smooth gearshifting
- reduces transmission noise
- wide viscosity range
- good corrosion protection
- high efficiency
- guarantees low fuel consumption

Specifications / Approvals

API GL5 • MIL-L 2105 C • MIL-L 2105 D

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 59 °F	0,855 g/cm³ DIN 51757
Viscosity at 104 °F	80 mm²/s ASTM D 7042-04
Viscosity at 212°F	14,3 mm²/s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	185 DIN ISO 2909
Pour point	-70 °F DIN ISO 3016
Flash point	374 °F DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

Universal use in motorbike transmissions and final drives where a gear oil according to current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Available pack sizes

1 l Can plastic	20086 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com