

Motorbike Gear Oil SAE 75W-140 (GL5)

Description

Fully Synthetic, GL5 high-performance extreme-pressure gear oil. Facilitates smooth and precise shifting even in extreme conditions, provides excellent wear protection properties and ideal viscosity-temperature behavior.

Properties

- outstanding corrosion protection
- reduces transmission noise
- excellent wear resistance
- wide viscosity range

legally binding.



Specifications / Approvals

API GL5

Technical data

SAE class (gear oils)	75W-140 SAE J306
Density at 59 °F	0,875 g/cm ³ DIN 51757
Viscosity at 104 °F	179 mm ² /s ASTM D 7042-04
Viscosity at 212°F	25 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	172 DIN ISO 2909
Pour point	-59 °F DIN ISO 3016
Flash point	406 °F DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Areas of application

Universal use in motorbike transmissions and final drives where a gear oil according to current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Available pack sizes

1 l Can plastic 20088
USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not