Product information

PI 29/08/18/2026

Motorbike Fork Oil SAE 10W Medium



Description

Full synthetic, medium-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

Properties

- high wear resistance
- good corrosion protection
- prevents foam formation
- prevents seals from swelling
- better drivability

Technical data

Density at 59 °F	0,83 g/cm³ ASTM D 7042-04
Viscosity at 104 °F	28,5 mm²/s DIN 51757
Viscosity at 212°F	5,7 mm²/s ASTM D 7042-04
Viscosity index	146 DIN ISO 2909
Pour point	-43 °F DIN ISO 3016
Flash point	471 °F DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes and other powersport vehicles where an oil with current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Available pack sizes

1 l Can plastic	20092 CAEN-CAFR-USEN
20 l Canister plastic	20404 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com