

Radiator Stop Leak

Description

Will immediately seal small leaks caused by external damage, porous solder joints and hairline cracks in cooling systems of all water cooled engines. Coolant is prevented from entering the combustion chamber due to internal leaks from head gasket etc. It does not react with oxygen or heat and will never prevent system flow or cause overheating. Radiator Stop Leak works as long as it's in the coolant.



Our information is based on thorough research and may be considered reliable, although not legally binding.

Properties

- compatible with conventional coolants and antifreezes
- suitable for aluminum radiators
- permanently and reliably seals hairline cracks and small leaks
- no negative side effects on the water pump or heating circuit
- for preventive use

Technical data

Form	liquid
Color / appearance	white, cloudy
Density at 68 °F	1,05 g/cm ³
Solubility in water	mixable
Odor	weak
Flash point	>100 °F

Areas of application

Used for sealing small leaks in cooling circuits of passenger motor vehicles, commercial vehicles, buses and two-wheel vehicles. Also suitable for cooling circuit with filters (exception: "Low Conductivity"-coolants).

Comment

⚠ WARNING: Reproductive Harm -
www.P65Warnings.ca.gov.

Application

Shake well before use. Add contents to the cold cooling system. Start up the heater. Then drive the vehicle for at least 10 minutes. Contents (250 ml) is sufficient for 10 Liters (2.6 gal.) coolant.

Available pack sizes

250 ml Can sheet metal	20132 USA-EN
250 ml Can sheet metal	20332 CANADA-EN-F