

Pro-Line Automatic Transmission Cleaner

Description

A highly effective formulation developed for safe internal cleaning of automatic transmissions during maintenance service. Eliminates problems and restores proper shifting performance in automatic transmissions. Allows the fresh oil to immediately develop full performance. Maintains operating efficiency, smooth shifting and overall behavior while maximizing longevity.



Properties

- gentle cleaning
- assures optimum shifting performance
- does not attack rubber and plastic seals
- optimizes economical use
- easily dissolves stubborn dirt

Technical data

Base	additive, naphtha-base special oil
Viscosity index	204
Viscosity at 104 °F	58 mm ² /s
Viscosity at 212°F	11,8 mm ² /s
Form	flüssig, liquid
Odor	characteristic
Density at 59 °F	0,885 g/ml

Areas of application

Suitable for most automatic transmission fluids. Using Liqui Moly Gear Tronic will guarantee best product performance and proper servicing. For professional use only.

Application

At operating temperature, add sufficient amount of Pro-Line Automatic Transmission Cleaner to existing fluid. With drive wheels in the air, start the engine and let it idle for 10 to 15 minutes. During this time, shift through all gears once or twice. Stop the engine, change the oil and replace filter according to the manufacturer's instructions. 100 ml used with 2 - 3 Liters (2.1 to 3.2 U.S. qt) of transmission fluid.

Available pack sizes

1 l Can sheet metal 20224
USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.