Product information
Speed Tec Gasoline

PI 51/08/18/2026



Description

High-tech fuel additive, developed specifically for improved throttle response under partial engine load. Optimizes fuel atomization and combustion, cleans fuel system while providing maximum engine performance and efficiency.

Properties

- improves acceleration
- optimizes engine performance
- contains no organometallic compounds
- ideal with catalytic converters
- no effect on octane number
- better drivability

Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light brown
Density at 59 °F	0,825 g/cm³
Flash point	>63 °F
Odor	characteristic
Form	liquid
Viscosity at 104 °F	<7 mm²/s

Areas of application

Suitable for use in all 4- and 2-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF).

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Contents (250 ml) is sufficient for 25–75 Liters (7 gal. to 20 gal.) fuel. For consistent use when refueling. Can be mixed with the fuel at any time.

Available pack sizes

250 ml Can sheet metal	20234 USEN
250 ml Can sheet metal	20340 CAEN-CAFR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com