

Truck Series Diesel Performance and Protectant

Description

An effective mixture of additives that clean and maintain diesel fuel systems. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

Properties

- removes undesirable residues
- prevents build-up of deposits
- protects expensive components against wear and corrosion
- increases smooth operation
- increases cetane number
- reduces pollutant emissions

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	-32 °F
Form	liquid
Odor	characteristic

Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

Comment

⚠ WARNING: Cancer - www.P65Warnings.ca.gov.

Application

Contents (500 ml) is sufficient for 25–150 Liters (7 gal. to 40 gal.) diesel. Effect lasts up to 2,000 km (1,200 miles).

Available pack sizes

500 ml Can sheet metal 20254
USA-EN



Our information is based on thorough research and may be considered reliable, although not legally binding.