Product information

PI 33/09/25/2026

Truck Series Diesel Performance and Protectant



Description

An effective mixture of additives that clean and maintain diesel fuel systems. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

Our information is based on thorough research and may be considered reliable, although not legally binding.

Properties

- increases cetane number
- removes undesirable residues
- prevents build-up of deposits
- protects expensive components against wear and corrosion
- increases smooth operation

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	-32 °F
Form	liquid
Odor	characteristic

Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). Fully compatible with all common diesel fuels, including R99 diesel.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

One full Can (500 ml) used with 30 – 150 liters (8 gal. to 40 gal.) of fuel. For a lasting effect we recommend to use at least every 2,000 km (1,200 miles).

Available pack sizes

500 ml Can sheet metal	20254 USEN

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com