

## Power Steering Oil Leak Stop

### Description

Keeps rubber and plastic seals in hydraulic power steering systems soft and pliable. Leaks caused by hardened and brittle seals are prevented or eliminated. Cleans internal oil passages to allow proper oil flow, reduces noise levels and extends service life while reducing repair costs.

### Properties

- minimizes unwanted noise
- cleans and maintains
- regenerates seals
- prevents rapid aging of oil
- prevents oil loss
- good corrosion protection
- increases service life

### Technical data

Color / appearance	brown
Viscosity at 104 °F	~ 166 mm <sup>2</sup> /s DIN 51562
Viscosity at 212°F	~ 26 mm <sup>2</sup> /s DIN 51562
Density	0,888 g/ml
Refractive index at 68 °F	~ 1,478
Form	liquid
Odor	characteristic

### Areas of application

Suitable for steering gears that are filled with Dexron II, Dexron III, Dexron VI or central hydraulic system oils.

### Application

Add to the compensating reservoir of the steering system. Contents (35 ml) is sufficient for 1 l (1.2 U.S. QT) power steering fluid.

### Available pack sizes

35 ml Tube plastic	20284 USA-AND-CANADA-EN-F
--------------------	------------------------------

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

