Product information

PI 17/08/18/2026

Motorbike Shock Absorber Oil Race



Description

Fully synthetic shock absorber oil. Prevents deposit build-up while reducing friction and wear. Foaming is prevented even during extreme conditions. The unique formulation allows better handling and rider feedback which allows easier suspension tuning. Fluid color is blue.

Properties

- outstanding corrosion protection
- high wear resistance
- increases driving safety
- prevents build-up of deposits
- outstanding viscosity stability
- very compatible with seals
- prevents foam formation

Technical data

Density at 59 °F	0,825 g/cm³ DIN 51757
Viscosity at 104 °F	17,4 mm²/s ASTM D 7042-04
Viscosity at 212°F	3,95 mm²/s ASTM D 7042-04
Viscosity index	124 DIN ISO 2909
Demulgation characteristics at 129 °F	< 20 min DIN ISO 6614
Pour point	-81 °F DIN ISO 3016
Flash point	428 °F DIN ISO 2592
Color / appearance	blue

Areas of application

Designed for racing or extreme motorbike and powersports use and when a fluid according to current product specifications is required or recommended.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted. Professional use only.

Available pack sizes

1 l Can plastic	20290 CAEN-CAFR-USEN
20 l Canister plastic	20292 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com