Product information
Electronic Spray

PI 34/08/18/2026

Description

Fully synthetic, silicone free contact spray, formulated for use on vehicle electronic and general electrical systems. Reduces fretting and corrosion, suppresses moisture. It is neutral to paints, common plastics and rubber. Cleans and protects electrical connectors.



Properties

- good corrosion protection
- silicone-free
- drives out moisture
- cleans contaminated contacts
- good water separation
- penetrates layers of oxides and sulphides
- reduces contact resistance

Technical data

Color / appearance	blue
Base	synthetic oil
Viscosity at 104 °F	49,5 mm²/s
Viscosity at 212°F	7 mm²/s
Viscosity index	145
Pour point	-63 °F DIN ISO 3016
Evaporation loss (Noack)	2,1 Gew.-% DIN ISO 2909
Water content	40 ppm Ω · cm DIN 51 581
Neutralization number	0,03 mg KOH/g DIN 51 777 T 1
Copper corrosion	0-1 DIN 51 809
Specific electrical volume resistance at 68 °F	1,6 · 10⁹ Ω · cm
Odor	characteristic
Form	liquid

Areas of application

Suitable for use on vehicle electronic and general electrical systems.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Spray components before installing them. If the contacts are heavily corroded, allow the product to act for longer and rub off corrosion residues with a cloth or brush.

Note: After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

Available pack sizes

200 ml Can aerosol	20298 USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com