Product information

PI 7/08/18/2026

Snowbike Motor Oil SAE 0W-40



Description

Fully synthetic low-friction motor oil designed for quick lubrication on cold start. The combination of high quality synthetic base oils together with an advanced additive package produces a low viscosity motor oil with high shear stability. This high-quality blend prevents engine deposits. Engine wear is reduced to a minimum thanks to low friction and heat.

Properties

- outstanding engine cleanliness
- outstanding lubrication reliability
- ideal with catalytic converters
- optimum oil pressure under all operating conditions
- instant lubrication after cold start
- outstanding high temperature stability
- excellent wear protection
- extremely low evaporation loss

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

API SN • JASO MA2

Technical data

SAE class (engine oils)	0W-40 SAE J300
Density at 59 °F	0,845 g/cm³ DIN 51757
Viscosity at 104 °F	76,5 mm²/s ASTM D 7042-04
Viscosity at 212°F	13,7 mm²/s ASTM D 7042-04
Viscosity at -31 °F (CCS)	<6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
HTHS at 302 °F	≥ 3,5 mPas ASTM D 5481
Pour point	-43 °F DIN ISO 3016
Flash point	438 °F DIN ISO 2592
Evaporation loss (Noack)	13 % ASTM D 5800-08 Method B
Total base number	6,4 mg KOH/g DIN ISO 3771
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

For 4-stroke Snowbike engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20356 CAEN-CAFR-USEN
4 l Canister plastic	20358 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com