Product information

Gear Oil (GL5) 75W-80

PI 26/09/30/2022

Description

GL5 SAE 75W-80 Gear Oil is a high-performance highpressure gear oil based on synthetic and mineral base oils and high-quality additives. Enables smooth and precise shifting action even in low temperatures. Can also be used to deal with unwanted noise and to solve gear-changing problems.

Properties

- excellent viscosity/temperature properties
- for eliminating shifting problems
- outstanding resistance to oxidation
- outstanding friction characteristics
- outstanding corrosion protection
- very good low-temperature properties
- excellent wear resistance
- optimum stability to aging

Specifications / Approvals

API GL5 • MIL-L 2105 C

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Peugeot Citroen (PSA) B71 2315 • Peugeot Citroen (PSA) B71 2330

Technical data

SAE class (gear oils) 75W-80 **SAE J306** Density at 15 °C 0,870 g/cm³ DIN 51757 Viscosity at 40 °C 61.0 mm²/s

ASTM D 7042-04

Viscosity at 100 °C $9.7 \, \text{mm}^2/\text{s}$

ASTM D 7042-04

< 150000 mPas

Viscosity at -40 °C (Brookfield)

ASTM D 2983-09

Viscosity index 1/10

DIN ISO 2909

-42 °C Pour point

DIN ISO 3016

210 °C Flash point

DIN ISO 2592

Color number (ASTM) L2.5

DIN ISO 2049

Areas of application

Specially developed for use in Peugeot and Citroen manual transmissions. Can also be used in other manual transmissions to deal with unwanted noise and to solve gear-changing problems. Usage

according to the prescribed specifications from the unit or vehicle manufacturer.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Can plastic 3658

D-GB-I-E-P

1 l Can plastic 20463

PL-H-RO-TR

20 l Canister plastic 3690

D-GB

21259 20 l Canister plastic

ALGERIEN-GB-ARAB-F

205 l Black plate barrel 21457

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de