Product information
Marine Gasoline Stabilizer

PI 36/09/28/2026



Description

Provides long-term protection against fuel aging and oxidation. Protects fuel system from corrosion and prevents problems during long term storage. When added to gasoline it uses its organic content to stabilize the fuel.

Properties

- protects fuel against oxidation and aging
- has a lasting effect
- cost-effective due to exact dosage
- simple to use
- ideal with catalytic converters

Technical data

Base	additive mixture in carrier liquid
Color / appearance	blue
Odor	characteristic
Form	liquid
Density at 59 °F	0,822 g/cm³
Hazard class as per German VbF	A III
Flash point	>61 °F
Viscosity at 104 °F	<7 mm²/s

Areas of application

Suitable for all 2- stroke and 4-stroke engines. Safe with catalytic converters.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Filling the dosage chamber once is sufficient for 5 liters (5.25 U.S. QT) of fuel (mixing ratio 1: 200). Add to fuel and let the engine idle for approx. 10 minutes.

Available pack sizes

1 l Can sheet metal	20502 USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com