Product information

PI 27/10/22/2026

Marine High Performance Gear Oil SAE 85W-90



Description

Special high-performance gear lube specifically for marine use. Formulated with a unique additive package that guarantees outstanding wear protection even if contaminated with water. Stable under extreme pressure, high stress and at high speeds. Offers outstanding corrosion protection and very good oxidation resistance. Fluid color is blue.

Properties

- stable to aging and stable viscosity
- outstanding corrosion protection
- excellent viscosity/temperature properties
- excellent high-pressure and wear protection properties
- high pressure-absorption capability

Technical data

SAE class (gear oils)	85W-90 SAE J 306
Density at 59 °F	0,88 g/cm³ DIN 51757
Viscosity at 104 °F	163,5 mm²/s ASTM D 7042-04
Viscosity at 212°F	15,5 mm²/s ASTM D 7042-04
Viscosity at 10 °F (Brookfield)	<= 150000 mPas ASTM D 2983-05
Viscosity index	96 DIN ISO 2909
Pour point	-16 °F DIN ISO 3016
Flash point	435 °F DIN ISO 2592
Color / appearance	blue

Areas of application

For transmissions where a high-performance gear lube with current product specifications is required or recommended. Specifically suited for Mercury outboard motors as of 75 hp output as well as MerCruiser Z-drives. Can be used as a replacement for a high-performance gear lube with viscosity SAE 90.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Can plastic	20536 CAEN-CAFR-USEN
20 l Canister plastic	20492 CAEN-CAFR-USEN
60 l Black plate barrel	20493 CAEN-CAFR-USEN
205 l Black plate barrel	22524 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com