Product information
Marine ATF

PI 31/09/24/2026

Description
Fully synthetic ATF fluid specially developed for marine use. Offers increased corrosion protection, high thermal stability and minimizes wear compared with conventional hydraulic fluids. Ensures excellent protective properties and guarantees proper hydraulic function. Compatible with all common sealing materials.



Properties
- optimum stability to aging
- universal application
- minimizes wear
- excellent corrosion protection
- highest thermal stability
- good material compatibility

Specifications / Approvals
ZF TE-ML 04D • ZF approval number ZF004927

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:
Allison C4 • Dexron II D • Dexron II E • Dexron III G • Dexron III H • Dexron TASA (Typ A/Suffix A) • Mariner • MerCruiser • Mercury

Technical data

Density at 59 °F	0,845 g/cm³ DIN 51757
Viscosity at 104 °F	36,0 mm²/s ASTM D 7042-04
Viscosity at 212°F	7,5 mm²/s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016
Flash point	428 °F DIN ISO 2592
Sulfate ash	0,1 g/100g DIN 51575
Shear stability, viscosity at 212 °F after 100 h	5,4 mm²/s DIN 51350-06-KRL/C
Color / appearance	red

Areas of application
For drives and transmissions such as reverse gears, steering systems, trim systems, hydrostatic transmission ratios as well as hydraulic and mechanical systems where a fluid meeting current product specifications is required.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application
Observe the manufacturers instructions!

Available pack sizes

1 l Can plastic	20544 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com