Product information

PI 47/11/12/2026

Marine 4T Motor Oil SAE 25W-40



Description

High performance motor oil formulated with specific synthetic marine additives. Provides a stable lubricating film and best wear protection in the most extreme conditions. Maintains engine rubber seals for lowest possible oil consumption.

Properties

- ideal with catalytic converters
- outstanding corrosion protection
- outstanding oil film strength
- stable to aging and stable viscosity
- optimum oil pressure under all operating conditions

Specifications / Approvals

API SM • NMMA FC-W Catalyst Compatible®

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Honda Marine • Mercury Marine • NMMA FC-W • Selva • Suzuki Marine • Tohatsu • Volvo Penta • Yamaha

Technical data

SAE class (engine oils)	25W-40 SAE J300
Density at 59 °F	0,875 g/cm³ DIN 51757
Viscosity at 104 °F	120,0 mm²/s ASTM D 7042-04
Viscosity at 212°F	13,5 mm²/s ASTM D 7042-04
Viscosity at 14 °F (CCS)	<= 13000 mPas ASTM D 5293
Viscosity index	110 DIN ISO 2909
HTHS at 302 °F	>= 3,7 mPas ASTM D 5481
Pour point	-16 °F DIN ISO 3016
Evaporation loss (Noack)	6 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575

Technical data

Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

For 4-stroke gasoline engines, where an oil according to current product specifications is required or recommended. Safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	20546 CAEN-CAFR-USEN
4 l Canister plastic	20548 CAEN-CAFR-USEN
20 l Canister plastic	20499 CAEN-CAFR-USEN
60 l Black plate barrel	25029 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	25057 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com