

Pro-Line Ceramic High Performance Lube Spray

Description

Synthetic high-performance lubricant with ceramics that is extremely adherent and penetrative. Suitable for a wide range of applications, e.g. on rails and slide rails as well as guides and hinges made of metal, plastic and rubber. Prevents stick-slip and, thanks to the high pressure and temperature resistances as well as the excellent water resistance, ensures a long lasting lubricant film. The solid lubricant ensures very good damping and emergency running characteristics.



Our information is based on thorough research and may be considered reliable, although not legally binding.

Properties

- universal application
- excellent adhesion
- good corrosion protection
- wide operating temperature range
- suppresses noise and vibration
- good water resistance
- has a lasting effect
- highest load-carrying capacity
- silicone-free
- does not contain resins

Technical data

Base	synthetic oil, ceramics
Color / appearance	white-beige
Propellant	propan, butan
Operating temperature range	-30 - +180, intermittent to +200
Odor	characteristic

Areas of application

Universally used in the automotive sector as well as by craftsmen. For lubricating with tight tolerances and eliminating squeaking, popping and creaking of hinges, joints, rods, steering levers, door check straps, etc.

Comment

Follow the relevant instructions of the vehicle manufacturer.

Application

Shake can well before use. Spray an appropriate amount onto the previously cleaned parts that have to be treated. Even greater penetrative effectiveness can be obtained by reducing the spraying distance. After use, turn over and spray clear.

Available pack sizes

400 ml Can aerosol 20612
DA-EN-FI-NO-SV