Product information

Coolant Ready Mix RAF 11

LIQUI MOLY

Description

Premixed product based on ethylene glycol. Antifreeze that does not contain amines, nitrites or phosphates and offers outstanding protection against frost, corrosion and overheating thanks to its special inhibitor package. Enables safe, year-round vehicle operation.

Costant Ready Mix RAF 11 White Costant Ready Mix Costant Ready Mix

Properties

- prevents operational malfunctions
- contains no amines, nitrites or phosphates
- ready for use
- outstanding corrosion protection
- provides outstanding protection against overheating
- prevents the cooling system from freezing up
- for extended change intervals (note manufacturer's instructions)

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Alfa Romeo 9.55523 • Behr • BMW GS 94000 • Chrysler MS-7170 • Cummins 85T8-2 • Deutz DQC CA-14 • Fiat 9.55523 • IVECO 18-1830 • JI Case JIC-501 • Lada/Avtovaz TTM VAZ 1.97.717-97 • Lancia 9.55523 • MTU MTL 5048 • Opel/GM GME L 46014 • Perkins • Saturn • Toyota Motor Corporation • Vauxhall GMEL1301 • Volvo Cars 128 6083 / 002 • Volvo Construction • Volvo Trucks

Technical data

Base ethylene glycol with inhibitors

Color / appearance bluegreen

Density at 20 °C 1,05 g/cm³

Shelf life in original sealed 36 months container

Frost protection < -20 °C

Areas of application

For all cooling systems and engines (including aluminum engines) in cars, commercial vehicles, buses, agricultural machinery as well as stationary engines and equipment that require cooling system protection of this quality.

Application

Clean cooling system with Radiator Cleaner (part no. 3320). Then drain the cooling system, flush it thoroughly with water and fill with Coolant Ready Mix RAF 11. Disposal according to the local regulations. Change interval according to manufacturer's instructions. Coolant Ready Mix RAF 11 is miscible and

compatible with radiator antifreeze containing silicates with quality VW designation G11, VW specification TL 774-C (LIQUI MOLY Radiator Antifreeze KFS 11) or with silicate-free radiator antifreeze from the original products in accordance with the VW specification TL 774-D/F (LIQUI MOLY Radiator Antifreeze KFS 12+ or Coolant Ready Mix RAF 12+).

PI 37/11/13/2023

Available pack sizes

Titulian to parott oillo	
1 l Canister plastic	20660 D-GB
5 l Canister plastic	8809 D-GB-I-E-P
20 l Canister plastic	8822 D-GB-I-E-P
200 l Black plate barrel	8823 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.