

Motorbike 4T SAE 5W-40 HC Street

Description

Fully synthetic high-performance motor oil provides optimum performance and engine protection in all operating conditions. Ensures outstanding engine cleanliness, excellent friction behavior and minimum wear together with perfect clutch operation, and smooth gear shifting.

Properties

- guarantees low oil consumption
- high shear stability
- high wear resistance
- optimum stability to aging
- optimum lubrication under all operating conditions
- outstanding engine cleanliness
- ideal with catalytic converters
- especially suitable for wet clutches

Specifications / Approvals

API SN PLUS • JASO MA2

Technical data

SAE Viscosity	5W-40 SAE J300
Density at 59 °F	0,850 g/cm ³ DIN 51757
Viscosity at 104 °F	85,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	14,3 mm ² /s ASTM D 7042-04
Viscosity index	175 DIN ISO 2909
Viscosity at -22 °F (CCS)	<= 6600 mPas ASTM D 5293
Pour point	-36 mPas DIN ISO 2909
Evaporation loss (Noack)	11,0 % ASTM D 5800 B
Flash point	442 °F DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current



specifications is required or recommended. Safe with catalytic converters.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20412 USA-AND-CANADA-EN-F
4 l Canister plastic	20414 USA-AND-CANADA-EN-F
20 l Canister plastic	20416 USA-AND-CANADA-EN-F
60 l Black plate barrel	22043 USA-AND-CANADA-EN-F
205 l Black plate barrel	22069 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.