Product information

Classic Transmission Oil SAE 140



Description

Mineral-based transmission oil specially designed for classic vehicles and motorcycles. Provides a stable lubricating film and minimizes wear. Offers very good lubrication properties and optimum corrosion protection. Enables smooth gearshifting.

Properties

- minimizes wear
- reduces running noise
- good corrosion protection
- does not attack common sealing materials
- also suitable for classic motorcycles



API GL1 • API GL2 • API GL3

Technical data

SAE class (gear oils) 140

SAE J306

Density at 15 °C 0,9 g/cm³

DIN 51757

Viscosity at 40 °C 390 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 27,4 mm²/s

ASTM D 7042-04

Viscosity index 96

DIN ISO 2909

Pour point -9 °C

DIN ISO 3016

Flash point 250 °C

DIN ISO 2592

Color number (ASTM) L 3,5

DIN ISO 2049

Areas of application

For transmissions in classic vehicles and motorcycles (especially manual transmissions) and axle drives with a low load in which a transmission oil compliant with API GL1/GL2/GL3 is required.

Application

When selecting the product, note the viscosity class and specification stipulated by the transmission manufacturer. Mixable with all branded gear oils. Full effectiveness only achieved when the product is used on its own (i.e. no mixing).

Available pack sizes



Available pack sizes

1 l Can plastic 20817

D-GB-I-E-P

PI 15/12/01/2021

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de