Product information

PI 43/11/02/2026

Anti-bacterial Diesel additive



Description

Broad-spectrum biocide effective against bacteria, yeasts, and molds in diesel fuel. **Use biocides safely. Always read the label and product information before use.**

Properties

- prevents bacterial, yeast, and mold growth in tank systems
- preserves contaminated tank systems
- keeps injection nozzles clean
- improves the lubrication properties
- prevents expensive repairs

Technical data

Base	biocide, detergent and cetan number enhancer
Color / appearance	brown, clear
Density at 15 °C	0,8991 g/cm³
Kinematic viscosity at 40°C	<7 mm²/s
Flash point	< 63 °C
Regulation on Flammable Liquids Class (Germany)	A III
Shelf life in original sealed container	5 years
Odor	characteristic
Form	liquid

Areas of application

For preventive use in diesel-powered vehicles which are decommissioned for long periods or are infrequently used such as construction machinery, commercial vehicles, RVs, passenger cars or in storage tanks or for disinfection of contaminated tank systems. Not suitable for use with HVO diesel fuel.

Application

Dosage: 1:1,000. 25 ml is sufficient for 25 L of diesel fuel. For preventive treatment, add the appropriate amount before refuelling. In the event of severe bacterial and fungal contamination causing filter blockages, apply a shock treatment (dosage 1:200; 125 ml is sufficient for 25 L of diesel fuel).

Available pack sizes

125 ml Can sheet metal	20940 EL-IT
1 l Can sheet metal	2368 DA-EN-FI-NO-SV
1 l Can sheet metal	21317 DE-EL-FR-IT

Available pack sizes

5 l Canister plastic	21318 DE-EN-ES
60 l Black plate barrel	21319 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com