Product information

PI 17/10/01/2026

Pro-Line JetClean Gasoline Intake System Cleaner



Description

Highly effective additive blend for use with JetClean Tronic II. Removes typical dirt and deposits from the intake and throttle valve areas. Dissolves and removes all greasy contamination, such as oil, resin, adhesive, and more. Ensures the proper functioning of moving parts. Increases the operational reliability of gasoline-powered engines.

Properties

- tested for turbochargers and catalytic converters
- simple to use
- rapid cleaning
- excellent cleaning effect
- cleaning possible without dismantling
- ready for use

Technical data

Form	liquid
Viscosity at 40 °C	<7 mm²/s
Odor	characteristic
Density at 15 °C	0,894 g/cm³
Flash point	-18 °C
Color / appearance	light yellow

Areas of application

For the intake and throttle valve area. Only for use in gasoline engines!

Application

Ready to use undiluted in the JetClean Tronic II. For detailed instructions on further use, see the JetClean Tronic II operating instructions.

Available pack sizes

300 ml Can sheet metal	20985 DE-EN-ES

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com