Product information

PI 18/09/15/2026

Pro-Line JetClean Diesel Intake System Cleaner



Description

Highly effective additive combination for direct use with the JetClean Tronic II. Removes typical contamination and deposits in the intake and throttle valve area. Loosens and removes dry and greasy contamination such as soot, oil, etc. Ensures the operability of all moving parts and reduces fuel consumption. Increases the reliability of diesel-powered engines.

Our information is based on thorough research and may be considered reliable, although not legally binding.

Properties

- simple to use
- rapid cleaning
- tested for turbocharger
- excellent cleaning effect
- cleaning possible without dismantling
- ready for use
- suitable for diesel particulate filters

Technical data

Form	liquid
Viscosity at 40 °C	<7 mm²/s
Odor	characteristic
Density at 15 °C	0,83 g/cm³
Flash point	<21 °C
Color / appearance	light yellowish

Areas of application

For the intake and throttle valve area. Only for use in diesel engines!

Comment

Ready for use for undiluted filling of the JetClean Tronic II. A detailed description of further application is given in the instructions of the JetClean Tronic II.

Application

Ready for use for undiluted filling of the JetClean Tronic II. A detailed description of further application is given in the instructions of the JetClean Tronic II.

Available pack sizes

300 ml Can sheet metal	20986 DE-EN-ES

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com