

Viscoplus Heavy Duty Formula

Description

Modern, mono-functional high-performance additive for stabilizing the viscosity of motor oils. Viscoplus Heavy Duty Formula offers outstanding protection against mechanical and therefore permanent shear losses to the oil under extreme running conditions and is effective against the thinning of motor oils due to frequent cold starts.



Properties

- fully compatible with mineral and synthetic oils
- reduces wear
- stabilizes loss of viscosity
- improves seals around moving engine parts

Technical data

Color / appearance	orange clear
Density at 20 °C	0,89 g/cm ³ DIN 51757
Viscosity at 40 °C	299,6 mm ² /s ASTM D7042
Flash point	120 °C DIN ISO 2592
Pour point	-15 °C DIN ISO 3016
Odor	characteristic
Form	liquid

Areas of application

For all passenger vehicles and commercial vehicles, gasoline and diesel engines in new and used vehicles.

Comment

Not suitable for use on motorbikes with wet clutches.

Application

Can contents (1 l) are sufficient for up to 20 liters of motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

Available pack sizes

1 l Can sheet metal	2105
	D-GB-I-E-P
1 l Can sheet metal	2697
	D-PL-H-RO-TR

Our information is based on thorough research and may be considered reliable, although not legally binding.