Product information

Diesel Hot-Climate 20W-50



Description

Diesel-Hot-Climate SAE 20W-50 is an all season, high-performance motor oil for using in diesel engines with and without exhaust gas turbocharging. Selected base oils and a high additive content guarantees optimum lubrication under extreme operating conditions and during long periods between oil changes.

ICUI MOTOR OIL Made in German

Properties

- excellent cold-start behavior
- miscible with all commercially available motor oils
- outstanding oil film strength
- universal application
- outstanding engine cleanliness
- very good dispersion properties
- can be used in gasoline and diesel engines with and without turbocharger
- stable to ageing and stable viscosity
- high wear resistance

Specifications / Approvals

ACEA A3/B4, E2 • API SL • API CF • API CG-4 • Allison C4 • MIL-L 2104 E

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar TO-2 • MAN 271 • MB 228.3

Technical data

SAE class (engine oils) 20W-50 SAE J300

Density at 15 °C 0,880 g/cm³
DIN 51757

Viscosity at 40 °C 165,0 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 18,5 mm²/s

ASTM D 7042-04

Viscosity at -20 °C (MRV) < 60000 mPas

ASTM D4684

Viscosity at -15 °C (CCS) ≤ 9500 mPas

ASTM D5293

Viscosity index 125

DIN ISO 2909

HTHS at 150°C \geqslant 3,7 mPas

ASTM D5481

Pour point -30 °C

DIN ISO 3016

Evaporation loss (Noack) 7,2 %

CEC-L-40-A-93

Technical data

Flash point 230 °C

DIN ISO 2592

Total base number 10,2 mg KOH/g

PI 29/04/18/2023

DIN ISO 3771

Sulfate ash 1,0 - 1,6 g/100g

DIN 51575

Color number (ASTM) L5,5

DIN ISO 2049

Areas of application

Universal motor oil for diesel engines (aspirated diesel engines and diesel engines with exhaust-gas turbocharging, with and without charge air cooler). Especially suitable where there are long intervals between oil changes and extreme operating conditions.

Application

The operating instructions of the vehicle and engine manufacturers must be followed.

Available pack sizes

60 l Black plate barrel 2113

D-GB

205 l Black plate barrel 2112

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.