

Top Tec MTF 5300 70W-75W

Description

Fully synthetic, low-viscosity high-performance transmission fluid. Thanks to excellent shear stability, offers high potential fuel savings and optimum wear protection. Ensures outstanding shifting comfort under all operating conditions thanks to the good viscosity-temperature properties.

Properties

- outstanding shifting comfort under all operating conditions
- guarantees low fuel consumption
- excellent shear stability
- excellent wear resistance
- outstanding corrosion protection
- excellent viscosity/temperature properties
- excellent synchronous behavior
- outstanding resistance to oxidation

Specifications / Approvals

API GL4

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

VW G 052 171 • VW G 052 527

Technical data

| | |
|----------------------------------|---|
| SAE class (gear oils) | 70W-75W SAE J306 |
| Density at 15 °C | 0,845 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 30,8 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 5,9 mm ² /s ASTM D 7042-04 |
| Viscosity at -55 °C (Brookfield) | < 150000 mPas ASTM D 2983-09 |
| Viscosity index | 139 DIN ISO 2909 |
| Pour point | < -60 °C DIN ISO 3016 |
| Flash point | 220 °C DIN ISO 2592 |
| Color number (ASTM) | L 2,5 DIN ISO 2049 |

Areas of application

Used especially for manual and automated manual transmissions (DSG). Recommended particularly for use in vehicles from Audi, Seat, Škoda and



Volkswagen.

Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

| | |
|-------------------------|---------------------|
| 1 l Can plastic | 21359 D-GB-I-E-P |
| 20 l Canister plastic | 21360 BOOKLET |
| 60 l Black plate barrel | 21361 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.