Product information

Top Tec ATF 1950

PI 26/11/13/2026



Description

ATF for ideal performance thanks to a premium combination of active agents. The reduced viscosity increases efficiency. The outstanding stability of the friction coefficient enables extended oil change intervals.

Properties

- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MB 236.17

Technical data

Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	20,0 mm²/s ASTM D7042
Viscosity at 100 °C	4,4 mm²/s ASTM D7042
Viscosity at -40 °C (Brookfield)	<= 10000 mPas ASTM D2983
Viscosity index	135 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	200 °C DIN ISO 2592
Color / appearance	brown

Areas of application

For the new generation of the Mercedes-Benz 9-speed automatic transmissions, model 725.0/1.

Available pack sizes

1 l Can plastic	21378 DE-ES-IT-PT
1 l Can plastic	21694 DA-FI-NO-SV
20 l Canister plastic	21379 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com