Product information
Klima Refresh

PI 33/11/12/2026



Description
Quickly frees the air conditioning of unpleasant odors that are caused by bacteria and mold in air conditioning systems, ventilation ducts or vehicle interiors. Simple to use without removal of the pollen or dust filter. Promotes pleasantly fresh air.

Properties
- assures fresh, clean air
- frees the air conditioning of odors that are caused by mold and bacteria
- increases ride comfort

Technical data

Color / appearance	yellow
Base	alcoholic solution of special surfactants and fragrances
Odor	characteristic
Form	aerosol
Shelf life in original sealed container	24 months

Areas of application
For vehicle air conditioning systems and interiors. On vehicles with ionization device or ionizer, this function must be switched off before use. For intended use only.

Comment
No persons are allowed in the vehicle during the spraying process!

Application
Start the engine and switch on the air conditioning (AC). Set the temperature regulator to “cold” and set the air distribution to windshield (top), maximum output and circulating air. If the vehicle is equipped with an ionization device or ionizer, this function must be switched off before use. Shake can vigorously before use and use the box to position it in the intake area of the air circulation system (usually the front passenger footwell or center console) so that the can sprays upwards with no obstruction. Actuate the spray head with the windows closed, leave the vehicle and close the doors. Open the doors after 10 min, switch off the engine, and ventilate the interior of the vehicle for approx. 10 min.

Available pack sizes

51 g Can aerosol	23309 AUEN-EN
75 ml Can aerosol	20000 DE-EN-ES-IT-PT

Available pack sizes

75 ml Can aerosol	21464 DA-EN-FI-NO-SV
75 ml Can aerosol	21465 DE-EN
75 ml Can aerosol	21466 AR-EL-EN-FR-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com