

Diesel Particulate Filter Protector

Properties

- protects the diesel particulate filter
- regeneration aid for diesel particulate filters
- especially suitable for short trips and city vehicles

Technical data

Color / appearance	red-brown
Odor	characteristic
Density at 20 °C	0,795 g/cm ³
Flash point	> 63 °C
Viscosity at 40 °C	1,3750 mm ² /s
Shelf life in original sealed container	36 months

and may be considered reliable, although not legally binding.



Areas of application

For diesel vehicles with diesel particulate filters, provided they are not equipped with an electronically controlled additive tank system for filter regeneration, such as those used in Citroën and Peugeot vehicles. Suitable for HVO and XTL diesel fuels.

Comment

Not suitable for vehicles equipped with an additive-based regeneration system (EOLYS®). Do not combine with LIQUI MOLY Diesel Particulate Filter Protector, Diesel Smoke Stop, or Diesel Smoke Stop C. The color of the product may vary. This will not affect the quality or effectiveness of the product.

Application

Add to the fuel every 2,000 km just before refueling. The contents of the can are sufficient to treat 50–70 liters of diesel fuel.

Note: Do not exceed the recommended dosage or use this product with Diesel Smoke Stop or System Care Diesel.

Available pack sizes

250 ml Can sheet metal	2146 DE-ES-PT
250 ml Can sheet metal	2650 BG-DE-PL
250 ml Can sheet metal	5148 DE-FR-NL
250 ml Can sheet metal	7180 EL-EN-IT
250 ml Can sheet metal	8349 DA-FI-NO-SV
250 ml Can sheet metal	21270 DE-HU-RO

Our information is based on thorough research