

LCP Anti-Corrosion Spray Oil

Description

Low viscosity special oil with excellent creep properties. Lubricates, maintains, protects and provides excellent corrosion protection, even in hard-to-reach areas. Also suitable as a rust remover. Can be used for ferrous and non-ferrous metals. Free of waxes and silicones. Very good material compatibility on various substrates, such as painted surfaces, metals, seals and plastics.



Properties

- self-sealing, non-drying protective film
- no surfaces for liquids to attack
- economical to use, thus saving time and costs
- outstanding resistance to salt water
- drives out moisture
- good lubricating qualities
- can be removed with solvents and aqueous industrial cleaners

Technical data

Density at 20 °C	0,78 g/ml
Color / appearance	brown
Form	liquid

Areas of application

For vehicles, machines, equipment, precision tools, measuring devices and molds in workshop, industry, handcraft, shipping, agriculture, household, garden and fishing gear. Also ideal for the preservation of semi-finished and finished parts made of steel and iron during intermediate storage, both outdoors and under cover.

Application

Can be applied by spraying. The solvent evaporates to leave behind a stable, highly adhesive oil film with outstanding anti-corrosion properties. If necessary, check for material compatibility at an inconspicuous place. The oil film can be easily removed, e.g. with LIQUI MOLY Universal Cleaner (part no. 1653).

Available pack sizes

300 ml Can aerosol 21653
D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.