Product information
Power Foam

PI 19/09/23/2026

Description
Thanks to its powerful foaming action, it stays on the painted surface longer and works more intensively. This helps loosen contamination such as insect residue, oil, and grease more effectively, making it much easier to clean the vehicle. With a pleasant orange scent. Resistant to frost down to +4 °C. Complies with VDA Class A and Class B requirements.



Technical data

Color / appearance	green
Odor	citrus
pH value	11,3
Density	1,033 g/ml
Frost resistance	up to 4 °C
Shelf life in original sealed container	36 months

Areas of application
For use with an automatic metering unit in stationary/self-service car washes as well as using manual dosing in spray appliances.

Application
Use undiluted via a metering pump. Usage approx. 8-10 ml per vehicle. With manual application via a spray appliance, choose the optimum setting for the air, water and cleaner to achieve the desired foam result. Dosage depending on the foaming equipment either undiluted or pre-diluted in a ratio of 1:4 to 1:9 (chemical:water). Max. application time according to VDA Guideline: 1 min. Do not allow product to dry!

Available pack sizes

25 l Canister plastic	21711
	DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com