Product information

PI 17/11/20/2026

Motorbike 4T 10W-50 Street

Description

High-performance motor oil. For maximum performance and protection of the engine under all operating conditions. Ensures optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear. Ensures smooth engagement and disengagement as well as gear shifting. Tested on engines with catalytic converters.



Properties

- optimum stability to aging
- tested for the use with catalytic converters
- high wear resistance
- optimum lubrication under all operating conditions
- guarantees low oil consumption
- high shear stability
- Optimum engine cleanliness
- especially suitable for wet clutches

Specifications / Approvals

API SP • JASO MA2

Technical data

SAE class (engine oils)	10W-50 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	120,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	18,5 mm²/s ASTM D 7042-04
Viscosity index	170 DIN ISO 2909
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
HTHS at 150°C	⩾ 3,7 mPas ASTM D 5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN 51578
Oil base	Advanced Full Synthetic

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without wet clutches.

Application

The operating instructions of the vehicle and engine manufacturers must be followed. Optimum performance is guaranteed only when used unmixed.

Available pack sizes

1 l Canister plastic	21725 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	23239 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	21726 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	23240 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21727 DE-EN-ES-FR-IT-PT
60 l Black plate barrel	21728 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com