

# Product information

## Grinding Paste

PI 7/02/28/2024



### Description

As effective problem solver, this paste effortlessly repairs heavily weathered paintwork, deep scratches, and orange peel and smooths the paint surface. Treated surfaces can then be painted directly. Silicone-free and suitable for polishing machines.



### Properties

- suitable for polishing machines
- easy removal of weathered paint layers
- simple to use
- prepares surfaces for painting
- smooths the paint surface

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Technical data

Base	grinding agent, solvents
Form	viscous
Color / appearance	white
Odor	characteristic
Density	1,1 g/cm <sup>3</sup>
Flash point	> 90 °C
Shelf life in original sealed container	30 months

### Areas of application

For repairing deep scratches, orange peel, and extremely weathered paintwork.

### Comment

Use care when working with polishing machines, as Grinding Paste 1500 has a strong abrasive effect.

### Application

1. Surfaces must be thoroughly cleaned with Car Wash Shampoo and carefully dried before treatment. 2. Shake well before use. 3. Then pour Grinding Paste 1500 onto a Hand Polishing Sponge Hard (part no. 21782) or Microfiber Cloth (part no. 1651) and apply thinly and uniformly using circular motions. Note: Take care at joins in the bodywork as the product is very abrasive! 4. After application, polish off the polish residues with Paintwork Microfiber Cloth (part no. 21783). Recommendation: Then seal with Hard & Protective Wax to provide longer protection for the paint. Note: Do not use under direct heat or on hot paint surfaces!

### Available pack sizes

250 ml Tube plastic 21758  
D