Product information Scratch Remover

Description

For removing deep scratches, paint mist, and grind marks on paintwork as well as for cleaning heavily weathered paintwork. Suitable for polishing machines.

Properties

- smoothes the paint surface
- easy removal of heavily weathered paint layers
- removes severe scratches
- silicone-free
- easy to polish
- simple to use

Technical data

Base	Abrasives, wax
Form	viscous
Color / appearance	violet
Odor	characteristic
Density	1,04 g/ml
Flash point	> 90 °C
Shelf life in original sealed container	30 months

Areas of application

For heavily scratched and weathered paintwork.

Application

1. Surfaces must be thoroughly cleaned with Car Wash Shampoo and carefully dried before treatment. 2. Shake well before use. 3. Then pour Scratch Remover 2000 onto a Hand Polishing Sponge Hard (part no. 21782) or Microfiber Cloth (part no. 1651) and apply thinly and uniformly using circular motions. Note: Take care at joins in the bodywork as the product is very abrasive! 4. After application, polish off polish residues with Paintwork Microfiber Cloth (part no. 21783). Recommendation: Then seal with Hard & Protective Wax to provide longer protection for the paint.

Note: Do not use under direct heat or on hot paint surfaces!

Our information is based on thorough research and may be considered reliable, although not legally binding.

PI 7/02/28/2024



