Product information

PI 8/09/16/2026

Gasoline System Cleaner LPG



Description

Special additive for cleaning and protecting gasoline engines against corrosion, particularly in LPG-powered vehicles. Removes heavy deposits from direct and port fuel injection systems. Protects the fuel injection system against malfunctions and failures. Restores the engine's original performance. Stabilizes the fuel and protects it against oxidation and premature degradation.

Properties

- removes deposits from entire fuel system
- prevents corrosion in the fuel system
- excellent aging protection

Technical data

Shelf life in original sealed container	60 months
Color / appearance	yellow, clear
Odor	aromatic odor
Density at 15 °C	0,816 g/ml
Flash point	>63 °C

Areas of application

For all gasoline engines powered by gasoline or LPG. Suitable for direct and port fuel injection systems. Add directly to the fuel tank.

Application

Can be added to the fuel at any time. Mixing takes place automatically. 300 ml sufficient for max. 75 l of fuel.

Available pack sizes

300 ml Can sheet metal	21786 BG-DE-PL
300 ml Can sheet metal	21787 EN-ES-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com