Product information

PI 16/10/21/2026

DEF Anti Crystal Additive Concentrate



Description

Ash-free combination of additives for the prevention of malfunctions in the SCR system of diesel engines. Reduces the formation of deposits in the AdBlue® tank and AdBlue® injection system. Guarantees extremely fine atomization of the urea solution by lowering the surface tension. Optimizes the return flow of the AdBlue® into the system, thereby minimizing the risk of AdBlue® crystallization.

AdBlue® registered Trademark of VDA Verband der Automobilindustrie e.V., Berlin, Germany

Technical data

Color / appearance	colourless
Shelf life in original sealed container	36 months
Density at 20 °C	1,0093 g/ml
Form	liquid
Odor	characteristic
Flash point	>63 °C

Areas of application

For all SCR systems that are operated with 32.5 % urea solution (AdBlue®, DEF).

Comment

Frost sensitive. Shake at room temperature to disperse deposits on bottom!

Application

Add 0.25 % to the AdBlue® solution (1:400). 25 ml is sufficient for 10 l of AdBlue®. 250 ml is sufficient for 100 l of AdBlue®. 2.5 l is sufficient for 1000 l of AdBlue®. For long-term application. Do not add to fuel! When adding to the AdBlue® tank, should ideally be added after the filling process. Due to the high concentration of active ingredients, foaming may occur under unfavorable conditions. Therefore, check components for suitability beforehand.

Available pack sizes

250 ml Dispensing bottle plastic	21799 AR-DA-DE-EN-FI-FR-IT-NL-NO-SV
250 ml Dispensing bottle plastic	21838 CS-EL-ES-HU-PL-PT-RO-RU-TR
2,5 l Canister plastic	21800 DA-DE-EN-ES-FI-IT-NL-NO-PL-PT-SV
2,5 l Canister plastic	21968 DA-EN-FI-NO-SV

Available pack sizes

200 l Drum plastic	29522 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com