Product information
DEF Anti Crystal Additive

PI 7/01/08/2026



Description
Ash-free combination of additives for the prevention of malfunctions in the SCR system of diesel engines. Reduces the formation of deposits in the AdBlue® tank and AdBlue® injection system. Improves the operability at low temperatures and guarantees extremely fine atomization of the urea solution by lowering the surface tension. Optimizes the return flow of the AdBlue® into the system, thereby minimizing the risk of AdBlue® crystallization.

AdBlue® registered Trademark of VDA Verband der Automobilindustrie e.V., Berlin, Germany

Technical data

Base	tenside, improves freezing point
Color / appearance	clear, colourless
Density at 15 °C	1,041 g/ml
Refractive index at 20 °C	1,432
Form	liquid
Odor	characteristic

Areas of application
For all SCR systems that are operated with 32.5 % urea solution (AdBlue®, DEF).

Comment
Frost sensitive. Shake at room temperature to disperse deposits on bottom!

Application
Add 1 % to the AdBlue® solution. 100 ml is sufficient for 12-15 l of AdBlue®. For long-term application. Do not add to fuel! When adding to the AdBlue® tank, should ideally be added after the filling process.

Available pack sizes

100 ml Bottle plastic	21801 EN-IT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com