Product information

PI 4/02/20/2026

Camping Top-up Oil 5W-30



Description

Synthetic high-tech motor oil for refilling on the go. Provides excellent protection against wear and ensures the optimal engine performance in motor homes, camping vans, and passenger cars. Exceeds even the highest test requirements of well-known vehicle manufacturers, assures reliable operation of the particulate filter (PF), and ensures maximum service life of the engine, even under extreme loads such as additional trailer load.

Properties

- outstanding engine cleanliness
- optimum oil pressure under all operating conditions
- tested for turbochargers and catalytic converters
- excellent wear resistance
- miscible with all commercially available motor oils

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

ACEA C2, C3 • API SQ • BMW Longlife-04 • Fiat 9.55535-S1 • Fiat 9.55535-S3 • Ford WSS-M2C 917-A • GM dexos2 • MB 229.31 • MB 229.51 • MB 229.52 • Opel OV 040 1547 - G30 / Opel OV 040 1547 - D30 • VW 505 00 • VW 505 01

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	71,0 mm²/s ASTM D7042
Viscosity at 100 °C	12,2 mm²/s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592

Technical data

Total base number	7,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

Areas of application

For gasoline and diesel engines, including vehicles with diesel particulate filter (DPF) – also if retrofit. Can be mixed with all commercially available motor oils. Tested for turbochargers and catalytic converters.

Application

For refilling with a low oil level. The specifications and instructions from the assembly or vehicle manufacturer must be followed.

Available pack sizes

1 l Canister plastic	21814 DE

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com