Product information

PI 16/11/23/2026

Top Tec 6310 0W-20



Description

Premium low-friction motor oil. Ensures optimal lubrication and excellent oil film stability even under extreme loads, while minimizing wear and deposits. Ideally suited for engines with start-stop system. Ensures maximum performance.

Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear protection
- high lubrication reliability
- high shear stability
- optimum stability to aging
- excellent high and low temperature behavior
- long engine service life
- optimum oil pressure under all operating conditions
- tested for turbochargers and catalytic converters

Specifications / Approvals

ACEA C5, C6 • API SP • Peugeot Citroen (PSA) B71 2010

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Fiat 9.55535-DM1 • Fiat 9.55535-GSX

Technical data

SAE class (engine oils)	0W-20 SAE J 300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	41,0 mm²/s ASTM D7042
Viscosity at 100 °C	8,1 mm²/s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	⩽ 6200 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	⩾ 2,6 mPas ASTM D5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	11,5 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592

Technical data

Total base number	9,8 mg KOH/g DIN ISO 3771
Sulfate ash	⩽ 0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

For gasoline, diesel, and hybrid vehicles. Specifically designed to meet the requirements of PSA PureTech and BlueHDi engines from model year 2018 onward, such as EB2xx and DV5Rxx engines from OPR 16886 (see ORGA calculator), which are also installed in Citroën, DS, Fiat, Jeep, Opel, and Peugeot vehicles. It can also be used in engines from other manufacturers.

Available pack sizes

1 l Canister plastic	21880 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21882 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21877 DE-EN-ES-IT-PT
60 l Black plate barrel	21878 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	21879 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com