Product information

PI 9/09/15/2026

Leichtlauf Performance 0W-20



Description

Low-friction motor oil for year-round use. Guarantees reliable lubrication, minimizes wear and keeps the engine clean. Guarantees excellent performance with low fuel consumption. Ideally suited for engines with start/stop system.

Properties

- outstanding engine cleanliness
- high lubrication reliability
- tested for turbochargers and catalytic converters
- excellent wear resistance
- good ageing stability

Specifications / Approvals

ACEA C5, C6 • API SP

Technical data

SAE class (engine oils)	0W-20 SAE J 300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	42,0 mm²/s ASTM D7042
Viscosity at 100 °C	8,1 mm²/s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	⩽ 6200 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	⩾ 2,6 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	13,0 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	8,0 mg KOH/g DIN ISO 3771
Sulfate ash	⩽ 0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

For gasoline, diesel and hybrid engines. Especially for European, Asian and American vehicles that stipulate lubricants that meet general specifications.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21883 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	21887 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21884 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	23218 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	21886 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com