Product information
Lock Care & De-Icer

PI 26/08/23/2024

Description
Specially developed spray grease for lubrication and care of installed lock cylinders and ignition locks. By using this care spray, moving parts will always operate smoothly. De-ices frozen door locks.



Our information is based on thorough research and may be considered reliable, although not legally binding.

Properties
- lasting corrosion protection
- does not attack plastics, rubber and paints
- outstanding lubricating action
- excellent de-icing properties
- friction and wear reducing

Technical data

Thickener	Li-soap
Base oil	Fully synthetic
Operating temperature range	-50 - +140 °C
Worked penetration	280 1/10 mm DIN ISO 2137
NLGI number	2 DIN 51818
Color / appearance	bright, slightly transparent
Dropping point	>185 °C
Base oil viscosity 40°C	ca. 30 mm²/s
Base oil viscosity 100°C	ca. 6 mm²/s
Flow pressure at -40 °C	>1400 mbar
Behavior in the presence of water	1-90
Four-ball tester material load/weld force	>2000 N

Areas of application
For the lubrication, care and de-icing of door locks, door hinges and mechanical side mirrors.

Comment
The technical specifications refer to the base grease after the solvent has flashed off and not to the aerosol can.

Application
Shake well before use. Insert the spray head in the lock barrel, push through and spray into the lock barrel.

Available pack sizes

50 ml Can aerosol	21925 GB

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com