

DIJectron

Description

The unique combination of proven PEA technology and the latest additive generation achieves maximum cleaning performance in the combustion chamber, **in** and **around** the injector tip and in the entire fuel system. Furthermore, DIJectron stops the formation of new deposits so that complex injector systems always work at the highest efficiency. Regular use of DIJectron significantly reduces the risk of engine damage caused by Low Speed Pre Ignition (LSPI), optimizes exhaust gas emissions and protects the fuel system from corrosion.



Properties

- better drivability
- excellent corrosion protection
- optimizes fuel consumption and exhaust emissions
- ideal with particulate filters and catalytic converters
- cleans the injection system
- assures precise atomization

Technical data

Base	additive mixture in liquid carrier
Color / appearance	yellowish, clear
Regulation on Flammable Liquids Class (Germany)	AIII
Flash point	> 145 °F
Pour point	ca. -49 °F
Form	liquid
Odor	characteristic

Areas of application

LIQUI MOLY recommends DIJectron particularly for modern 4-stroke gasoline direct injection (GDI) engines, with or without turbochargers.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Contents (300 ml) is sufficient for 40–70 Liters (10.5 gal. to 18 gal.) of fuel. For the best results and long term effect add DIJectron to the fuel tank every 4.000 km (2400 miles).

Available pack sizes

Available pack sizes

300 ml Can sheet metal	22076
	USEN
300 ml Can sheet metal	22110
	CAEN-CAFR

Our information is based on thorough research and may be considered reliable, although not legally binding.