

Top Tec ATF 1800 R

Description

Fully synthetic leading edge, high-performance automatic transmission fluid. Developed to meet the severe requirements of modern multi-speed transmissions designed with 6 or more gears. The use of modern additive technology provides ultimate protection, longer fluid life and stability combined with ideal shift quality under all operating conditions. Color: red.



Properties

- high wear resistance
- excellent viscosity/temperature properties
- high resistance to aging
- enables a multifaceted range of applications
- outstanding resistance to oxidation
- prevents foam formation
- very good low-temperature properties
- excellent corrosion protection
- outstanding friction characteristics

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Aisin Warner AW-1 • BMW 83 22 0 142 516 • BMW 83 22 2 152 426 • BMW 83 22 2 289 720 • BMW 83 22 2 305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 355 599 • BMW M-1375.4 • Dexron VI • Fiat 9.55550-AV5 • Ford Mercon LV • Honda ATF 3.1 • Honda ATF DW-1 • Honda Typ 3.0 • Hyundai SP-IV • Hyundai SP-IV-RR • Isuzu ATF WSI • JASO 1A-LV • JWS 3324 (Aisin Warner) • Land Rover TYK 500050 • Mazda ATF FZ • MB 236.12 • MB 236.14 • MB 236.82 • Mitsubishi Dia Queen ATF-MA1 • Mitsubishi Dia Queen ATF-PA • Nissan AT-Matic S Fluid • Nissan Matic P • Toyota WS • VW G 055 005 • VW G 055 162 • VW G 055 540 • VW G 060 162

Technical data

Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	27,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	5,7 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 15000 mPas ASTM D 2983-09
Viscosity index	155 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016

Technical data

Flash point	410 °F DIN ISO 2592
Color / appearance	red

Areas of application

For modern automatic transmissions, hybrid transaxle systems and electric drive differentials where a ATF fluid meeting current product specifications is required.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

Available pack sizes

20 l Canister plastic	22145 CAEN-CAFR-USEN
205 l Black plate barrel	22184 CAEN-CAFR-USEN
1.000 l Container	22185 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.